

Interior Lighting



UK Manufacture
5 YEAR WARRANTY

SIENNA Commercial LED Downlight



Image - SIENNA downlight with drop frosted lens and emergency pack

Ordering

SIE-XX-AA-BB-C-D

where
XX = Wattage

AA = LED Colour
CW = 5000K+, NW = 3500K-4000K, WW = 2700-3000K

BB = Diffuser Options
IF = Frosted Internal, IC = Internal Clear
EF = Frosted External (drop style), EC = Clear External (drop style)

C = Ceiling Mount
S = Suspended, P = Plasterboard

D = Emergency Operation
E = Has this feature, X = Not fitted

Example
SIE-14-NW-EF-E
14Watt, neutral white, with frosted drop diffuser and emergency function

Please call our sales desk on 08456 434740 to discuss ordering and technical issues such as the various sensor and dimming options

Applications

Offices interiors
Reception areas
Retail outlets and shopping centres
Conference Centres
Hotels Libraries
Restaurants
Hospitals
Corridors and stairwells

Description

The Earlsmann SIENNA down lights can replace up to the 2 x 26W CFL types. They emit no UV, run cool and have a service life up to 50,000 hours thus reducing maintenance. Due to their high efficiency, these luminaires are extremely environmentally friendly and can help with carbon reduction programmes.

Options include sensor controls dimming and full emergency operation.

Features

Low power consumption
Instant start
No flicker
Long life
No mercury
Minimal maintenance
Minimal glare

Benefits

Reduced energy bills, reduced CO2
Full brightness at turn on - improved safety
Improved working area comfort
Reduced maintenance costs
Simplified disposal at end of life
Reduced costs
Improved working area comfort

Specifications

| | |
|------------------------|------------------------------|
| Colour Temperature | Cool, Natural and Warm White |
| Colour Rendering Index | 80Ra |
| Voltage | 90-260Vac |
| Markings | CE ROHS |
| Efficacy | >80lm/W (typ) |
| LED | CREE module |
| Life | 50000hrs (L70) |
| Dimensions | 194mm dia. x 100 |
| Cutout | 164mm |
| Emergency | >100lm, 3hr non maintained |

Options

| | |
|----------------|---------------------------------------|
| Colour | Warm White, Natural White, Cool White |
| Lens | Opal, drop lens |
| Emergency | 3hour non-maintained |
| Mounting | Plaster board or suspended ceiling |
| Sensor Control | |
| Dimming | |

Sizes

| Power (Watts) | Output(Lm)CW | (equivalent to) |
|---------------|--------------|-----------------|
| 10 | 900 | 1x26W |
| 14 | 1300 | 2x18W |
| 20 | 1820 | 2x26W |

