



Electroluminescent Products


Super Bright EL Wire




Aqua




Blue



Red



Lime



Pink



Purple



Orange



White



Green

Support

if you would like to talk to someone about your application, additional power supplies not shown or discuss termination please call our Technical Department on 08456 434740

Applications

Bars - shelves, bar lighting
 Kitchens - undershelf, plinths,
 Signage
 Architecture - feature and accent lighting
 Interiors - cove, pelmet lighting
 Caravans
 Clothing

Description

The Earlsmann super bright EL wire is just 2.5mm diameter but is considerably brighter than many larger wires. It has a minimum bend radius of only 6mm making it extremely versatile and suitable for a wide range of applications from architectural high lighting to fashion accessories.

Features

2.5mm diameter
 6mm bend radius

Benefits

Discreet to fix
 Versatile

Termination

Each cut length of EL wire will need connecting to a supply. This is done by carefully stripping the insulation, soldering on a lead and applying insulating sleeving. If required, we can make these connections for you. Multiple connections available.

Power Supplies

| Model No. | Operating range (m) | Modes | Supply |
|-------------------------------|---------------------|-----------------------------|-------------|
| Battery | | | |
| KH1.5 | 0.1 - 1.0 | Flash & Continuous | 1.5V AAA |
| KH4 | 0.5 - 2.5 | Flash & Continuous | 3V AA |
| KD5 | 0.5 - 14.0 | Flash & Continuous | 6V AAA |
| KL10 | 0.1 - 15.0 | Variable Flash/Fade & Cont. | 9V PP3 |
| Mains & DC adapter | | | |
| KLAC8 | 0.5 - 6.0 | Fast/slow flash & Cont. | AC220-240V |
| KD5 | 0.5 - 14.0 | Flash & Continuous | 6V adapter |
| L10 | 5.0 - 20.0 | Flash & Continuous | 12V adapter |
| KD30B | 5.0 - 30.0 | Flash & Continuous | 12V adapter |
| KH200 | 100.0- 250.0 | Continuous | AC220-240V |

Accessories

We have a range of accessories for EL wire
 Splitters 1 inlet to 2, 3 or 4 outlets
 Extension leads 1, 3, 5m with connectors
 Connectors
 End caps
 Heatshrink sleeves