

# Emergency Lighting



**UK Manufacture**  
**5 YEAR WARRANTY\***

## Dual 2in1 emergency LED Bulkhead



### Dual 2 in 1 LED Emergency luminaire; ideal for small spaces

Earlsmann's Dual 2 in 1 LED Emergency luminaire is available for external and internal use and is ideal for small rooms and refuge areas.

It solves the dilemma of BS5266-1 6.3 which requires that, in the event of a power failure and to avoid the risk of occupants being left in complete darkness, light from at least 2 emergency luminaires, should be visible in each zone.

Key is the inclusion of a second, non maintained independent emergency circuit in a single housing. This saves the costly installation of 2 separate fittings; often impractical and unsightly in a small room.

The main light is a 15W LED bulkhead providing high lumen output in neutral white and offers significant power savings when compared with 28W fluorescent 2D lighting types. Options include microwave sensor and a 20% preset comfort level.

**Good to know** – A single dual 2 in 1 emergency LED luminaire will save on installation costs.

### Ordering

#### BCH-15NW-J-2E

where

<b>B</b>	Body type	DR= drum round, GAL = Galaxy
<b>C</b>	Body colour	B= Black, W = White,
<b>H</b>	Diffuser	P = Prismatic (drum only), O = Opal
<b>15</b>	Wattage	
<b>NW</b>	LED colour	4000K
<b>J</b>	Sensor	M = Microwave M20 = 20% preset
<b>2E</b>	Dual emergency	

Example

DRWP-15NW-2E

White round drum bulkhead 15W with prismatic diffuser, neutral white LED, Dual emergency

### Standards

Manufactured to comply with  
EN55015, EN61547, EN6100-3-2, EN61347-2-7, EN61347-2-3,  
BSEN60598

### Dual 2 in 1 emergency bulkheads are best for...

Bathrooms, small rooms, refuge areas, escape routes in  
Hotels, theatres and conference centres  
Cold stores and freezers  
Offices

Not sure the 2 in 1 emergency luminaire is right for your application.  
Give us a call to discuss your requirements.

\* 1 year on batteries

### Benefit from...

Low power consumption - **Reduced energy bills, reduced Co<sub>2</sub>**  
Long life with reduced maintenance - **Lower running costs**  
Instant start, full brightness at turn on - **Improved safety**  
2 in 1 design - **Comply with BS6266**

### Specifications

Emergency	
Output	2 x120lm lumens output
Status indicator	2 x Green LED
Battery life	1x 3 hour maintained, 1x non maintained
Charge time	24 hours
Supply	220-230V 50/60Hz

Galaxy style - interior use		
Dimensions	425 dia x 117	IP20

Bulkhead - exterior use		
Dimensions	321 dia x 97	IP65

LED	Epistar,
Output	1200lm
Power	15w
Efficacy	100lm/W (LED)
Colour temp	4000K
Colour rendering	80Ra
Life	50000 hrs L70

### Options

Microwave sensor	on/off or 20% preset
Daylight sensor	

### Output

<b>Total (W)</b>	<b>Output (lm)</b>
15	1200