

Emergency Lighting

3 YEAR WARRANTY



EMLED1 - 3hour maintained/non-maintained

Output	400lm - 120 em mode
Status indicator	Green LED
Power	6W
Efficacy	66lm/W (LED)
Colour temp	6500K
Life	30000 hrs
Charge time	24 hours
Battery type	NiCd
Supply	220-240V 50/60Hz
Dimensions	345x107x76
Base material	White polycarbonate
Sealing	IP65



EMLED3 - 3hour maintained/non-maintained

Output	160lm - 100lm em mode
Status indicator	Green LED
Power	4W
Efficacy	40lm/W (LED)
Colour temp	6500K
Life	30000 hrs
Charge time	24 hours
Battery type	NiCd
Supply	220-240V 50/60Hz
Dimensions	351x110x60
Base material	White polycarbonate
Sealing	IP65



EMLED2A - 3hour maintained/non-maintained

Output	125lm - 115lm em mode
Status indicator	Green LED
Power	3W
Efficacy	41lm/W (LED)
Colour temp	6000K
Life	25000 hrs
Charge time	24 hours
Battery type	NiCd
Supply	220-240V 50/60Hz
Dimensions	216x97x48
Base material	White polycarbonate
Sealing	IP65

LED Emergency Luminaire Range

Earlsmann provide a range of LED lighting suitable for most requirements

All have a 3 hour duration in emergency mode
Bulkheads are supplied with a full set of legends

Standards

Manufactured to comply with
EN55015, EN61547, EN6100-3-2, EN61347-2-7, EN61347-2-3,
BSEN60598



EMSW - 3hour maintained/non-maintained

Output	70lm
Status indicator	Green LED
Power	4W
Colour temp	6000K
Life	40000 hrs
Charge time	24 hours
Battery type	NiCd
Supply	220-240V 50/60Hz
Dimensions	222x332x25
Suspension	1.5m max
Base material	White polycarbonate
Sealing	IP20
Legend	Supplied with Up arrow others available



EMSUS - 3hour maintained

Output	13lm/8lm em mode
Status indicator	Green LED
Power	2W
Colour temp	5500K
Life	30000 hrs
Charge time	24 hours
Battery type	NiCd
Supply	220-240V 50/60Hz
Dimensions	185x300x45
Suspension	0.8m max
Base material	White polycarbonate
Sealing	Ip20
Legend	Supplied with Up arrow others available