

# Interior Lighting

## ACADEMY LED batten



**5 YEAR WARRANTY**  
**ECA compliant**


**Try the aesthetically pleasing ACADEMY LED batten**

The Academy LED batten fitting is a high performance, cost effective LED batten light designed for modern interiors.

It is an ultra-thin, lightweight, aesthetically pleasing fitting designed for commercial, education and retail environments and has lockable anti tamper design features for use in schools and colleges and other public areas.

This luminaire comes with a wide range of options including DALI/switchdim, integral microwave sensors and integral emergency and can be provided with CASAMBI bluetooth control, if required

**Good to know:** With a wide range of options continuity can be maintained throughout your site.



**Benefit from...**

Low power consumption - **Reduced energy bills, reduced CO<sub>2</sub>**  
Long life, reduced maintenance - **Lower running costs**  
Instant start, full brightness at turn-on - **Improved safety**

**Specifications**

Colour Temperature	NW 4000K,
Colour Rendering Index	80Ra
Sealing	IP40
Voltage	220-240Vac 50/60Hz
Markings	CE, RoHS
Efficacy	120 lm/W
LED life	50000 hours L80 B50 @ 25° C
Beam angle	120°
Ambient temp	-20°C / + 45°
Power factor	>0.95
Lens	Polycarbonate
Case	Mild steel, ABS endcaps
Colour	White

**Ordering**

**ACAD-D-E-I-J-K**

Where		
<b>D</b>	Model	2513, 3514, 4015,15016
<b>E</b>	Colour temp	NW
<b>I</b>	Dimming options	D4 = DALI/switchdim
<b>J</b>	Sensor options	ML = low, MH = high M20 = 20% preset DH = daylight harvesting
<b>K</b>	Emergency	E

Example  
ACAD2513NW-E = 25 watt with no sensors, 4000K, emergency pack

Photometric files are available upon request. Ask about Casambi bluetooth controls

**ACADEMY is best for...**

- Warehouses, factories and workshops
- Corridors
- Offices
- Schools

Not sure the ACADEMY is right for you? Give us a call to discuss your requirements.

Note - not all options may be available with some models. Please discuss your requirements with us

**Options**

Emergency	
Sensor	Microwave, preset light level (M20), Daylight harvesting,
Dimming	DALI/switchdim

**Output**

Model	Dim (mm)	Total W <sub>(max)</sub>	Output (lm)
2513	1200x175x75	25	3125
3514		36	4000
4015	1500x175x75	41	4700
5016		60	6000

