


# PRODUCT INFORMATION

## **Exterior Lighting**

### Brough LED Bulkhead

#### **Luminous Intensity**



Typical output

144 lx max 93 lx average 4000K neutral white Luminaire height 2.3m

#### **Ordering**

#### BEB-B-C-H-J-K

where

 B
 Model
 10/15/20

 C
 Body colour
 B= Black, W = White,

 H
 Style
 Y = eyelid,

J Sensor M K Emergency option E

Example

BEB15W-M-E

White round drum bulkhead 15W with white base, emergency pack and microwave sensor

Photometric files available up on request

### The Brough LED bulkhead light is best for...

Car parks and other public area and amenities Hotels and conference centres Corridors, walkways and stairwells Cold stores Stations and platform areas

Not sure if the Brough is right for your application. Give us a call to discuss your requirements.

#### **5 YEAR WARRANTY**

(not Battery)

#### Brough LED bulkhead lights for small spaces

Earlsmann's Brough LED bulkhead is suitable for external and internal use, from car parks and walkways to hotels and cold stores.

It is available as 9W, 14W or 20W versions to replace standard 9W, 28W and 38W 2D fittings and offers over 60% power savings when compared with traditional fluorescent types.

In addition, excellent reliability reduces costly maintenance bills.

Selectable CCT enables exactly the right colour temp. for every situation and reduces stock.

**Good to know** – add a microwave sensor option to your Brough LED lighting to achieve even greater energy savings.

#### Benefit from...

Low power consumption - **Reduced energy bills, reduced CO**<sub>2</sub> Long life with reduced maintenance - **Lower running costs** Instant start, full brightness at turn on - **Improved safety** 

### **Specifications**

Efficacy 95lm/W Colour Rendering Index 80Ra

Voltage 220-240Vac 50/60Hz
Markings CE, ROHS
LED life 50000hrs L70 B50

Power 9W/14W/20W

Colour Temp 3000/4000/5700 selectable

Power factor >0.9
Weight <1.5kg
Material Polycarbonate

Beam angle 115° Sealing IP65 Shock IK08

Ambient temp. -200°C to +45°C
Dimensions (mm) 10 256x75
15 315x75
20 380x82

#### **Options**

Microwave sensor on/of

Up to 10m range, 360°, 5sec to 10min

daylight threshhold off/30lux

Emergency

#### **Output**

Total (W)	Output (lm)4
9	810
14	1260
20	1930
	9 14

Earlsmann reserve the right to change the specification without notice

Rev 020323

