


PRODUCT INFORMATION

Interior Lighting

TONBRIDGE Lobay

Polar output



120°

Ordering

TLB -C-E-J

Where

С	Model/W	100, 135, 165
E	Colour temp	CW
1	Sensor ontions	SR - PTR

Accessories ACS214 trunking kit

Example

TLB100CW- 100W cool white

Photometric files are available upon request.

TONBRIDGE LED lobay are best for...

Warehouses and aisles, factories and workshops Supermarkets and other retail premises Indoor tennis courts, squash, badminton, equestrian etc Gymnasia Museums

Not sure the TONBRIDGE Lobay is right for your building? Give us a call to discuss your requirements.

5 YEAR WARRANTY

TONBRIDGE LED lobay - for industry and sport

The TONBRIDGE LED lowbay may be used in a variety of applications from sports facilities to workshops. A choice power rating provides a range of options to tailor this fitting to your requirements.

The beam profile makes it particularly suitable for lower mounting heights.

It is a highly efficient lighting unit, up to 145 Im/W, so reduces energy costs and helps achieve carbon reduction targets. With a design life of over 50,000 hours, it saves on maintenance costs too.

 $\label{eq:Good to know} - \text{The TONBRIDGE Lobay is an extremely versatile replacement for T8/T5 fluorescent lighting}$

Benefit from...

Low power consumption - Reduced energy bills, reduced CO₂ Minimal maintenance - Lower running costs Minimal heat production - Savings in air-con maintenance costs Instant start, full brightness at turn on - Improved safety

Specifications

Colour Temperature CW 5000K
Colour Rendering Index 80Ra
Sealing IP20
Shock IK0

Voltage 100-240Vac 50/60Hz

Markings CE, RoHS

Efficacy up to 145lm/W (system)
LED life 50000hrs L80B50
Ambient temp T_a -20°C / + 40°
Power factor >0.95 (full power)
Diffuser Polycarbonate
Body Powder coated steel

Colour White

Weight 3.1/3.6kg depending on model

Options

Sensor Dimming Emergency Wireguard Trunking mount kit

Output

Model	Power (W)	Output (lm)	Dims (mm)
100	100	14500	630x325x53
135	135	18900	630x325x53
165	165	22820	630x325x53

Earlsmann reserve the right to change the specification without notice

Rev 010121

